

LEICA DISTO D510

Specifications

- > ISO 16331-1 certified typical measuring accuracy ± 1 mm
- > ISO 16331-1 certified typical range up to 200 m
- > Measuring units 0.000 m, 0.0000 m, 0.00 m, 0.00 ft, 0'00" 1/32, 0.00 in, 0 in 1/32
- > Power Range Technology™ Yes
- > Distance in m 10, 50, 100 m
- > Ø of the laser dot in mm 6, 30, 60 mm
- > Tilt sensor measuring range 360°
- > Pointfinder with 4x zoom Yes
- > Memory Last 30 displays
- > Free App Yes
- > Data interface* Bluetooth® V4.0 Smart
- > Measurements per set of batteries up to 5000 (with Li-iron LFP batteries)
- > Multifunctional end-piece Automatic recognition
- > Batteries type AA 2 × 1.5 V (Ships with Li-ion rechargeable)
- > Tripod thread 1/4"- 20
- > Protection class IP65 – water jet protection and dust-tight
- > Dimensions 143 x 58 x 29 mm
- > EAN/UPC 7640110694237, 7640110694251 (North America)



@plazagps



@plazagps store



@plazagps01

PLAZA GPS

GPS, Telescope & Surveying

Mall WTC Matahari Serpong Lt.2 Blok S.20

Tip : 021-53153871

Whatsapp : 081298737575

Web : www.plazagps.com