

# Technical Specification



## LEICA DISTO S910 LASER METER

- Distance measurement
- Minimum / maximum measurements
- Area / volume measurements
- Painter function
- Tilt measurement
- Smart Horizontal Mode
- Sloped object measurement

Typ. measuring accuracy	± 1.0 mm / ~1/16"
Range	0.05 up to 300m / 2" to 984ft
X-Range Power Technology	●
Smart Base measuring range	
Horizontal	360°
Vertical	-40° to 80°
Distance in m	2, 5, 10m
Typical tolerance of the P2P function	2, 5, 10mm
Levelling range	± 5°
Pointfinder with 4x zoom	●
Overview camera	●
File formats	jpg, dxf

Memory for CAD files	20 files, each with 30 points
Free software for Windows	●
Free App	iOS / Android
Data interface*	Bluetooth® SMART, WLAN
Measurements per set of batteries	up to 4000**
Batteries	Li-ion rechargeable
Charging time	4h
Protection class	IP 54
Dimensions	164 x 61 x 32 mm / 6.45" x 2.4" x 1.26"
Weight with batteries	290g / 10.25oz



Laser class 2  
in accordance with IEC 60825-1

\* System requirements and other details can be found at [www.disto.com](http://www.disto.com)  
\*\* Reduced in Bluetooth® or WLAN mode

Free App: Tools for Pro\* & Leica DISTO™ sketch  
Mastering your jobsite challenges



\*Tools for Pro app not available on Google Play



PT. BIRUNI GEO PRATAMA

Mall WTC Matahari Serpong LT.2 Blok S.20 Tangerang Selatan  
Tlp 021.53153871 whatsapp : 081298737575 web : [www.plazagps.com](http://www.plazagps.com)